



# **Statement of Charges for Use of System for The Electricity Network Company Limited's Distribution Network**

This Statement is in a form  
to be approved by the Gas  
and Electricity Markets

## **FINAL STATEMENT**

Effective from: 1<sup>st</sup> April 2017

## Version Control

Version	Date	Description of version and any changes made
1.0	January 2016	Published Final

## Contents

<b>1.</b>	<b>Introduction .....</b>	<b>5</b>
	Validity period .....	6
	Contact details .....	6
<b>2.</b>	<b>Charge application and definitions .....</b>	<b>8</b>
	Supercustomer billing and payment .....	8
	Supercustomer charges .....	8
	Site-specific billing and payment .....	10
	Site-specific billed charges .....	10
	Time periods for half-hourly metered properties .....	11
	Time periods for pseudo half-hourly unmetered properties .....	12
	Application of capacity charges .....	12
	Chargeable capacity .....	12
	Exceeded capacity .....	13
	Demand exceeded capacity .....	13
	Generation exceeded capacity .....	13
	Standby capacity for additional security on site .....	14
	Minimum capacity levels .....	14
	Application of charges for excess reactive power .....	14
	Demand chargeable reactive power .....	15
	Generation chargeable reactive power .....	15
	Incorrectly allocated charges .....	16
	Generation charges for pre-2005 designated EHV properties .....	17
	Provision of billing data .....	17
	Out of area use of system charges .....	18
	Licensed distribution network operator charges .....	18
	Licence exempt distribution networks .....	19
	Full settlement metering .....	19
	Difference metering .....	19
	Gross settlement .....	20
	Net Settlement .....	21
<b>3.</b>	<b>Schedule of charges for use of the distribution system .....</b>	<b>22</b>
<b>4.</b>	<b>Schedule of line loss factors .....</b>	<b>23</b>
	Role of line loss factors in the supply of electricity .....	23
	Calculation of line loss factors .....	23
	Publication of Line loss factors .....	23
<b>5.</b>	<b>Notes for Designated EHV Properties .....</b>	<b>26</b>

EHV costs .....	26
Charges for new Designated EHV Properties.....	26
Charges for amended Designated EHV Properties .....	26
Demand-side management.....	26
<b>6. Electricity distribution rebates.....</b>	<b>28</b>
<b>7. Accounting and administration services .....</b>	<b>28</b>
<b>8. Charges for electrical plant provided ancillary to the grant of use of system.....</b>	<b>28</b>
<b>Appendix 1 - Glossary .....</b>	<b>29</b>
<b>Appendix 2 - Guidance notes .....</b>	<b>36</b>
Background.....	36
Meter point administration.....	36
Your charges.....	38
Reducing your charges .....	38
Reactive power and reactive power charges.....	39
Site-specific EHV charges.....	39
<b>Annex 1 - Schedule of Charges for use of the Distribution System by LV and HV Designated Properties.....</b>	<b>40</b>
<b>Annex 2 - Schedule of Charges for use of the Distribution System by Designated EHV Properties (including LDNOs with Designated EHV Properties/end-users).....</b>	<b>40</b>
<b>Annex 3 - Schedule of Charges for use of the Distribution System to Preserved/Additional LLFC Classes .....</b>	<b>40</b>
<b>Annex 4 - Charges applied to LDNOs with HV/LV end users .....</b>	<b>40</b>
<b>Annex 5 – Schedule of Line Loss Factors .....</b>	<b>40</b>
<b>Annex 6 - Un-scaled [nodal / network group] costs.....</b>	<b>40</b>

## 1. Introduction

- 1.1. This statement tells you about our charges and the reasons behind them. It has been prepared consistent with Standard Licence Condition 14 of our Electricity Distribution Licence. The main purpose of this statement is to provide our schedule of charges<sup>1</sup> for the use of our Distribution System and to provide the schedule of adjustment factors<sup>2</sup> that should be applied in Settlement to account for losses from the Distribution System. We have also included guidance notes in Appendix 2 to help improve your understanding of the charges we apply.
- 1.2. Within this statement we use terms such as 'Users' and 'Customers' as well as other terms which are identified with initial capitalisation. These terms are defined in the glossary.
- 1.3. The charges in this statement replicate those published by the DNOs where the latter have been calculated using the Common Distribution Charging Methodology (CDCM) for Low Voltage and High Voltage (LV and HV) Designated Properties. Charges for any Designated EHV Properties connected to the ENC network will be calculated using the ENC EHV Charging Methodology. At the date of publication ENC has no Designated EHV properties.
- 1.4. Separate charges are calculated depending on the characteristics of the connection and whether the use of the Distribution System is for demand or generation purposes. Where a generation connection is seen to support the Distribution System the charges will be negative and the Supplier will receive credits for exported energy.
- 1.5. The application of charges to premises can usually be referenced using the Charge Code contained in the charge tables. The Charge Code is applied by reference to the combination of the LLFC, PC and SSC attached to a supply point. Further information on how to identify and calculate the charge that will apply for your premise is provided in the guidance notes in Appendix 2.
- 1.6. All charges in this statement are shown **exclusive** of VAT. Invoices will include VAT at the applicable rate.

---

<sup>1</sup> Charges can be positive or negative.

<sup>2</sup> Also known as Loss Adjustment Factors or Line Loss Factors.

- 1.7. The annexes that form part of this statement are also available in spreadsheet format. This spreadsheet contains supplementary information used for charging purposes and a simple model to assist you to calculate charges. This spreadsheet can be downloaded from <http://www.gtc-uk.co.uk/about-us/our-regulated-businesses>.

### **Validity period**

- 1.8. This charging statement is valid for services provided from the effective date stated on the front of the statement and remains valid until updated by a revised version or superseded by a statement with a later effective date.
- 1.9. When using this charging statement care should be taken to ensure that the statement or statements covering the period that is of interest are used.
- 1.10. Notice of any revision to the statement will be provided to Users of our Distribution System. The latest statements can be downloaded from <http://www.gtc-uk.co.uk/about-us/our-regulated-businesses>.

### **Contact details**

- 1.11. If you have any questions about this statement please initially contact us at this address:

Regulation  
GTC  
Energy House  
Woolpit Business Park  
Woolpit  
Bury St Edmunds  
IP30 9UP  
[regulatory@gtc-uk.co.uk](mailto:regulatory@gtc-uk.co.uk)  
01359 243251

- 1.12. All enquiries regarding tariffs should be addressed to:

Finance Revenue  
GTC  
Energy House  
Woolpit Business Park  
Woolpit  
Bury St Edmunds  
IP30 9UP  
[Finance.Revenue@gtc-uk.co.uk](mailto:Finance.Revenue@gtc-uk.co.uk)

1.13. All enquiries regarding connection agreements and changes to maximum capacities should be addressed to:

MPAN Requests  
GTC  
Energy House  
Woolpit Business Park  
Woolpit  
Bury St Edmunds  
IP30 9UP  
[MPAN.Requests@gtc-uk.co.uk](mailto:MPAN.Requests@gtc-uk.co.uk)

1.14. For all other queries please initially contact our general enquiries telephone number: 01359 240363 lines are open 08:00 - 17:00 Monday to Friday.

## **2. Charge application and definitions**

- 2.1. The following section details how the charges in this statement are applied and billed to Users of our Distribution System.
- 2.2. We utilise two billing approaches depending on the type of metering data received. The 'Supercustomer' approach is used for Non-Half-Hourly (NHH) metered, NHH unmetered or aggregated Half-Hourly (HH) metered premises and the 'Site-specific' approach is used for HH metered or pseudo HH unmetered premises.
- 2.3. Typically NHH metered are domestic and small businesses, HH metered are larger businesses and unmetered premises are normally streetlights.

### **Supercustomer billing and payment**

- 2.4. Supercustomer billing and payment applies to metering points registered as NHH metered, NHH unmetered or aggregated HH metered. The Supercustomer approach makes use of aggregated data obtained from Suppliers using the 'Non Half Hourly Distribution Use of System (DUoS) Report' data flow.
- 2.5. Invoices are calculated on a periodic basis and sent to each User for whom we transport electricity through our distribution system. Invoices are reconciled over a period of approximately 14 months to reflect later and more accurate consumption figures.
- 2.6. The charges are applied on the basis of the combination of LLFC PC and SSC assigned to a Meter Point Administration Number (MPAN), and the units consumed within the time periods specified in this statement. These time periods may not necessarily be the same as those indicated by the Time Pattern Regimes (TPRs) assigned to the Standard Settlement Configuration (SSC. All LLFCs are assigned at our sole discretion.

### **Supercustomer charges**

- 2.7. Supercustomer charges include the following components:
  - a fixed charge - pence/MPAN/day; there will be only one fixed charge applied to each MPAN; and
  - unit charges, pence/kWh; more than one unit charge may apply depending on the type of tariff for which the MPAN is registered.



- 2.8. Users who supply electricity to a Customer whose metering system is:
- Measurement Class A or B, and settled on Profile Classes (PC) 1 through to 8; or
  - Measurement Class F or G;
- will be allocated the relevant charge structure set out in Annex 1.
- 2.9. Measurement Class A charges apply to Exit/Entry Points where NHH metering is used for Settlement.
- 2.10. Measurement Class B charges apply to Exit Points deemed to be suitable as Unmetered Supplies as permitted in the Electricity (Unmetered Supply) Regulations 2001<sup>3</sup> and where operated in accordance with Balancing and Settlement Code (BSC) procedure 520<sup>4</sup>.
- 2.11. Measurement Class F and G charges apply to Exit/Entry Points where HH aggregated metering data is used for Settlement.
- 2.12. Identification of the appropriate charge can be made by cross-reference to the ENC charge code.
- 2.13. Valid Settlement PC/SSC/Meter Timeswitch Code (MTC) combinations for LLFCs where the Metering System is Measurement Class A and B are detailed in Market Domain Data (MDD).
- 2.14. Where an MPAN has an invalid Settlement combination, the 'Domestic Unrestricted' fixed and unit charges will be applied as default until the invalid combination is corrected. Where there are multiple SSC/TPR combinations, the default 'Domestic Unrestricted' fixed and unit charges will be applied for each invalid TPR combination.
- 2.15. The time periods for unit charges where the Metering System is Measurement Class A and B are as specified by the SSC. To determine the appropriate charge

---

<sup>3</sup> The Electricity (Unmetered Supply) Regulations 2001 available from <http://www.legislation.gov.uk/uksi/2001/3263/made>

<sup>4</sup> Balancing and Settlement Code Procedures on unmetered supplies are available from <https://www.elexon.co.uk/bsc-related-documents/related-documents/bscps/>

rate for each SSC/TPR a lookup table is provided in the spread sheet that accompanies this statement<sup>5</sup>.

- 2.16. The time periods for unit charges where the Metering System is Measurement Class F and G are set out in the table 'Time Bands for Half Hourly Metered Properties' in Annex 1.
- 2.17. The 'Domestic Off-Peak' and 'Small Non-Domestic Off-Peak' charges are additional to either an unrestricted or a two-rate charge.

### **Site-specific billing and payment**

- 2.18. Site-specific billing and payment applies to Measurement Class C, D and E metering points settled as HH metered. The site-specific billing and payment approach to Use of System (UoS) billing makes use of HH metering data at premise level received through Settlement.
- 2.19. Invoices are calculated on a periodic basis and sent to each User for whom we transport electricity through our Distribution System. Where an account is based on estimated data, the account shall be subject to any adjustment that may be necessary following the receipt of actual data from the User.
- 2.20. The charges are applied on the basis of the LLFC, PC and SSC assigned to the MPAN (or the Meter System Identifier (MSID) for Central Volume Allocation (CVA) sites), and the units consumed within the time periods specified in this statement.
- 2.21. All LLFCs/GSP groups are assigned at our sole discretion. Where an incorrectly applied LLFC or GSP group is identified, we may at our sole discretion apply the correct LLFC/GSP group and/or charges.

### **Site-specific billed charges**

- 2.22. Site-specific billed charges may include the following components:
  - a fixed charge pence/MPAN/day or pence/MSID/day;
  - a capacity charge, pence/kVA/day, for Maximum Import Capacity (MIC) and/or Maximum Export Capacity (MEC);
  - an excess capacity charge, pence/kVA/day, if a site exceeds its MIC and/or MEC;

---

<sup>5</sup> Electricity Network Company - Schedule of Charges and Other Tables Final 2017-18

- unit charges, pence/kWh, more than one unit charge may be applied; and
  - an excess reactive power charge, pence/kVArh, for each unit in excess of the reactive charge threshold.
- 2.23. Users who wish to supply electricity to customers whose metering system is Measurement Class C, D or E or CVA will be allocated the relevant charge structure dependent upon the voltage and location of the metering point.
- 2.24. Measurement Class C, E or CVA charges apply to Exit/Entry Points where HH metering, or an equivalent meter, is used for Settlement purposes.
- 2.25. Measurement Class D charges apply to Exit points deemed to be suitable as Unmetered Supplies as permitted in the Electricity (Unmetered Supply) Regulations 2001<sup>6</sup> and where operated in accordance with BSC procedure 520<sup>7</sup>.
- 2.26. Fixed charges are generally levied on a pence per MPAN/MSID basis. Where two or more HH MPANs/MSIDs are located at the same point of connection (as identified in the connection agreement), with the same LLFC, and registered to the same supplier, only one daily fixed charge will be applied.
- 2.27. LV and HV Designated Properties will be charged in accordance with the CDCM and allocated the relevant charge structure set out in Annex 1.
- 2.28. Designated EHV Properties will be charged in accordance with the Electricity Networks Company's EHV Charging Methodology and allocated the relevant charge structure set out in Annex 2.
- 2.29. Where LV and HV Designated Properties or Designated EHV Properties have more than one point of connection (as identified in the Connection Agreement) then separate charges will be applied to each point of connection.

### **Time periods for half-hourly metered properties**

- 2.30. The time periods for the application of unit charges to LV and HV Designated Properties that are HH metered are detailed in Annex 1. If the incumbent DNO

---

<sup>6</sup> The Electricity (Unmetered Supply) Regulations 2001 available from <http://www.legislation.gov.uk/ukxi/2001/3263/made>

<sup>7</sup> Balancing and Settlement Code Procedures on unmetered supplies and available from <http://www.elexon.co.uk/pages/bscps.aspx>

has issued a notice to change time Bands, we will replicate such changes in our time bands. The details are set out in Annex 1.

- 2.31. The time periods for the application of unit charges to Designated EHV Properties are detailed in Annex 2. If the incumbent DNO has issued a notice to change time Bands, we will replicate such changes in our time bands. The details are set out in Annex 2.

### **Time periods for pseudo half-hourly unmetered properties**

- 2.32. The time periods for the application of unit charges to connections that are pseudo HH metered are detailed in Annex 1. If the incumbent DNO has issued a notice to change time Bands, we will replicate such changes in our time bands. The details are set out in Annex 1.

### **Application of capacity charges**

- 2.33. The following sections explain the application of capacity charges and exceeded capacity charges.

#### **Chargeable capacity**

- 2.34. The chargeable capacity is, for each billing period, the MIC/MEC, as detailed below.
- 2.35. The MIC/MEC will be agreed with us at the time of connection or pursuant to a later change in requirements. Following such an agreement (be it at the time of connection or later) no reduction in MIC/MEC will be allowed for a period of one year.
- 2.36. Reductions to the MIC/MEC may only be permitted once in a 12 month period. Where MIC/MEC is reduced the new lower level will be agreed with reference to the level of the customer's maximum demand. The new MIC/MEC will be applied from the start of the next billing period after the date that the request was received. It should be noted that, where a new lower level is agreed, the original capacity may not be available in the future without the need for network reinforcement and associated charges.
- 2.37. In the absence of an agreement, the chargeable capacity, save for error or omission, will be based on the last MIC and/or MEC previously agreed by the distributor for the relevant premise's connection. A customer can seek to agree

or vary the MIC and/or MEC by contacting us using the contact details in section 1.

### **Exceeded capacity**

- 2.38. Where a customer takes additional unauthorised capacity over and above the MIC/MEC, the excess will be classed as exceeded capacity. The exceeded portion of the capacity will be charged at the excess capacity charge p/kVA/day rate, based on the difference between the MIC/MEC and the actual capacity used. This will be charged for the full duration of the month in which the breach occurs.

### **Demand exceeded capacity**

$$\text{Demand exceeded capacity} = \max(2 \times \sqrt{AI^2 + \max(RI, RE)^2} - MIC, 0)$$

Where:

AI = Active Import (kWh)

RI = Reactive import (kVArh)

RE = Reactive export (kVArh)

MIC = Maximum import capacity (kVA)

- 2.39. Only reactive import and reactive export values occurring at times of active import are used in the calculation. Where data for two or more MPANs is aggregated for billing purposes the HH consumption values are summated prior to the calculation above. For sites which are importing and exporting in the same HH, i.e. where active import is not equal to zero and active export is not equal to zero, use zero for reactive import and reactive export when calculating capacity taken.
- 2.40. This calculation is completed for every half hour and the maximum value from the billing period is applied.

### **Generation exceeded capacity**

$$\text{Generation exceeded capacity} = \max(2 \times \sqrt{AE^2 + \max(RI, RE)^2} - MEC, 0)$$

Where:

AE = Active Export (kWh)

RI = Reactive import (kVArh)

RE = Reactive export (kVArh)

MEC = Maximum export capacity (kVA)

- 2.41. Only reactive import and reactive export values occurring at times of active export are used in the calculation. Where data for two or more MPANs is aggregated for billing purposes the HH consumption values occurring at times of kWh export are summated prior to the calculation above. For sites which are importing and exporting in the same HH, i.e. where active import is not equal to zero and active export is not equal to zero, use zero for reactive import and reactive export when calculating capacity taken.
- 2.42. This calculation is completed for every half hour and the maximum value from the billing period is applied.

#### **Standby capacity for additional security on site**


- 2.43. Where standby capacity charges are applied, the charge will be set at the same rate as that applied to normal MIC. Where, at the customer's request, for additional security of supplies requiring sterilisation of capacity at two different sources of supply, we reserve the right to charge for the capacity held at each source.

#### **Minimum capacity levels**

- 2.44. There is no minimum capacity threshold.

#### **Application of charges for excess reactive power**

- 2.45. When an individual HH metered MPAN's reactive power (measured in kVArh) at LV and HV Designated Properties exceeds 33% of total active power (measured in kWh), excess reactive power charges will apply. This threshold is equivalent to an average power factor of 0.95 during the period. Any reactive units in excess of the 33% threshold are charged at the rate appropriate to the particular charge.
- 2.46. Power Factor is calculated as follows:



2.47. The chargeable reactive power is calculated as follows:

**Demand chargeable reactive power**

$$\text{Demand chargeable kVArh} = \max\left(\max(RI, RE) - \left(\sqrt{\left(\frac{1}{0.95^2} - 1\right)} \times AI\right), 0\right)$$

Where:

AI = Active import (kWh)

RI = Reactive import (kVArh)

RE = Reactive export (kVArh)

2.48. Only reactive import and reactive export values occurring at times of active import are used in the calculation. For sites which are importing and exporting in the same HH i.e. where active import is not equal to zero and active export is not equal to zero, no calculation for that HH is made and the result for that HH would be zero.

2.49. The square root calculation will be to two decimal places.

2.50. This calculation is completed for every half hour and the values summated over the billing period.

**Generation chargeable reactive power**

$$\text{Generation chargeable kVArh} = \max\left(\max(RI, RE) - \left(\sqrt{\left(\frac{1}{0.95^2} - 1\right)} \times AE\right), 0\right)$$

Where:

AE = Active Export (kWh)

RI = Reactive Import (kVArh)

RE = Reactive Export (kVArh)

- 2.51. Only reactive import and reactive export values occurring at times of active export are used in the calculation. Where data for two or more MPANs is aggregated for billing purposes the HH consumption values are summated prior to the calculation above. For sites which are importing and exporting in the same HH i.e. where active import is not equal to zero and active export is not equal to zero, no calculation for that HH is made and the result for that HH would be zero.
- 2.52. The square root calculation will be to two decimal places.
- 2.53. This calculation is completed for every half hour and the values summated over the billing period.

#### **Incorrectly allocated charges**

- 2.54. It is our responsibility to apply the correct charges to each MPAN/MSID. The allocation of charges is based on the voltage of connection and metering information. We are responsible for deciding the voltage of connection while the Supplier determines and provides the metering information.
- 2.55. Generally, the voltage of connection is determined by where the metering is located and where responsibility for the electrical equipment transfers from us to the connected customer. This is normally established when the MPAN/MSID is created and will include information about whether the MPAN/MSID is for import or export purposes. Where an MPAN/MSID is used for export purposes the type of generation (intermittent or non-intermittent) will also be determined.
- 2.56. The Supplier provides us with metering information which enables us to allocate charges where there is more than one charge per voltage level. This metering data is likely to change over time if, for example, a Supplier changes from a two rate meter to a single rate meter. When this happens we will change the allocation of charges accordingly.
- 2.57. Where it has been identified that a charge is likely to be incorrectly allocated due to the wrong voltage of connection (or import/export details) then a correction request must be made to us. Requests from persons other than the



current Supplier must be accompanied by a Letter of Authority from the Customer; the existing Supplier must also be informed. Any request must be supported by an explanation of why it is believed that the current charge is wrongly applied along with supporting information, including, where appropriate photographs of metering positions or system diagrams. Any request to correct the current charge that also includes a request to backdate the correction must include justification as to why it is considered appropriate to backdate the change.

2.58. If it has been identified that a charge has been incorrectly allocated due to the metering data then a correction request should be made to the Supplier.

2.59. Where we agree that an MPAN/MSID has been assigned to the wrong voltage level then we will correct it by allocating the correct set of charges for that voltage level. Any adjustment for incorrectly applied charges will be as follows:

- Any credit or additional charge will be issued to the Supplier/s who were effective during the period of the change.
- The correction will be applied from the date of the request, back to the date of the incorrect allocation or, up to the maximum period specified by: the Limitation Act (1980), in England and Wales, which covers a six year period; or, the Prescription and Limitation (Scotland) Act 1973, which covers a five year period; whichever is the shorter.

2.60. Should we reject the request a justification will be provided to the requesting Party.

2.61. We shall not unreasonably withhold or delay any agreement to correct the charges applied and would expect to reach agreement within three months from the date of request.

#### **Generation charges for pre-2005 designated EHV properties**

2.62. Not Used

2.63. Not Used

#### **Provision of billing data**

2.64. Where HH metering data is required for UoS charging and this is not provided in accordance with the BSC or the Distribution Connection and Use of System

Agreement (DCUSA), such metering data shall be provided to us by the User of the system in respect of each calendar month within five working days of the end of that calendar month.

- 2.65. The metering data shall identify the amount consumed and/or produced in each half hour of each day and shall separately identify active and reactive import and export. Metering data provided to us shall be consistent with that received through the metering equipment installed.
- 2.66. Metering data shall be provided in an electronic format specified by us from time to time and, in the absence of such specification, metering data shall be provided in a comma-separated text file in the format of Master Registration Agreement (MRA) data flow D0036 (as agreed with us). The data shall be emailed to [Finance.Revenue@gtc-uk.co.uk](mailto:Finance.Revenue@gtc-uk.co.uk).
- 2.67. We require details of reactive power imported or exported to be provided for all Measurement Class C and E sites. It is also required for CVA sites and Exempt Distribution Network boundaries with difference metering. We reserve the right to levy a charge on Users who fail to provide such reactive data. In order to estimate missing reactive data, a power factor of 0.95 lag will be applied to the active consumption in any half hour.

#### **Out of area use of system charges**

- 2.68. Not Applicable

#### **Licensed distribution network operator charges**

- 2.69. Licensed Distribution Network Operator (LDNO) charges are applied to LDNOs who operate Embedded Networks within our Distribution Service Area.
- 2.70. The charge structure for LV and HV Designated Properties embedded in networks operated by LDNOs will mirror the structure of the All-the-way Charge and is dependent upon the voltage of connection of each embedded network to the host DNO's network. The same charge elements will apply as those that match the LDNO's end customer charges. The relevant charge structures are set out in Annex 4.
- 2.71. Where an MPAN has an invalid Settlement combination, the 'LDNO HV: Domestic Unrestricted' fixed and unit charges will be applied as default until the invalid

combination is corrected. Where there are multiple SSC/TPR combinations, the default 'LDNO HV: Domestic Unrestricted' fixed and unit charges will be applied for each invalid TPR combination.

2.72. The charge structure for Designated EHV Properties embedded in networks operated by LDNOs will be calculated individually using the EDCM. The relevant charge structures are set out in Annex 2.

2.73. For Nested Networks the relevant charging principles set out in DCUSA Schedule 21 will apply. <http://www.dcusa.co.uk/SitePages/Documents/DCUSA-Document.aspx>

### **Licence exempt distribution networks**

2.74. The Electricity and Gas (Internal Market) Regulations 2011 introduced new obligations on owners of licence exempt distribution networks (sometimes called private networks) including a duty to facilitate access to electricity and gas suppliers for customers within those networks.

2.75. When customers (both domestic and commercial) are located within an exempt distribution network and require the ability to choose their own supplier this is called 'third party access'. These embedded customers will require an MPAN so that they can have their electricity supplied by a Supplier of their choice.

2.76. Licence exempt distribution networks owners can provide third party access using either full settlement metering or the difference metering approach.

### **Full settlement metering**

2.77. This is where a licence exempt distribution network is set up so that each embedded installation has an MPAN and Metering System and therefore all customers purchase electricity from their chosen Supplier. In this case there are no Settlement Metering Systems at the boundary between the licensed Distribution System and the exempt distribution network.

2.78. In this approach our UoS charges will be applied to each MPAN.

### **Difference metering**

2.79. This is where one or more, but not all, customers on a licence exempt distribution network choose their own Supplier for electricity supply to their premise. Under this approach the customers requiring third party access on the exempt

distribution network will have their own MPAN and must have a HH Metering System.

2.80. Unless agreed otherwise, our UoS charges will be applied using gross settlement/net settlement or both.

### **Gross settlement**

2.81. Where one of our MPANs (27) is embedded within a licence exempt distribution network connected to our Distribution System, and difference metering is in place for Settlement purposes and we receive gross measurement data for the boundary MPAN, we will continue to charge the boundary MPAN Supplier for use of our Distribution System. No charges will be levied by us directly to the Customer or Supplier of the embedded MPAN(s) connected within the licence exempt distribution network.

2.82. We require that gross metered data for the boundary of the connection is provided to us. Until a new industry data flow is introduced for the sending of such gross data, gross metered data shall:

- be provided in a text file in the format of the D0036 MRA data flow;
- the text file shall be emailed to [Finance.Revenue@gtc-uk.co.uk](mailto:Finance.Revenue@gtc-uk.co.uk)
- the title of the email should also contain the phrase "gross data for difference metered private network".
- the text file and the title of the email shall contain the metering reference specified by us in place of the Settlement MPAN, i.e. a dummy alphanumeric reference to enable the relating of the gross metered data to a given boundary MPAN;
- the text filename shall be formed of the metering reference specified by us followed by a hyphen and followed by a timestamp in the format YYYYMMDDHHMMSS and followed by ".txt"; and

2.83. For the avoidance of doubt, the reduced difference metered measurement data for the boundary connection that is to enter Settlement should continue to be sent using the Settlement MPAN.

## **Net Settlement**

- 2.84. Where one of our MPANs (27) is embedded within a licence exempt distribution network connected to one of our distribution systems, and difference metering is in place for Settlement purposes, and we do **not** receive gross measurement data for the boundary MPAN, we will charge the boundary MPAN Supplier based on the net measurement for use of our Distribution System. Charges will also be levied directly to the Supplier of the embedded MPAN(s) connected within the licence exempt distribution network based on the actual data received.
- 2.85. The charges applicable for an embedded MPAN are unit charges only. These will be the same values as those at the voltage of connection to the licence exempt distribution network and are shown in Annex 1 and 2. The fixed charge and capacity charge, at the agreed MIC/MEC of the boundary MPAN, will be charged to the boundary MPAN supplier.

### **3. Schedule of charges for use of the distribution system**

- 3.1. Tables listing the charges for the distribution of electricity for UoS are published in the annexes to this document.
- 3.2. These charges are also listed in a spreadsheet which is published with this statement and can be downloaded from <http://www.gtc-uk.co.uk/about-us/our-regulated-businesses>.
- 3.3. Annex 1 contains charges applied to LV and HV Designated Properties.
- 3.4. Annex 2 contains the charges applied to our Designated EHV Properties and charges applied to LDNOs for Designated EHV Properties connected within their embedded Distribution System.
- 3.5. Annex 3 contains details of any preserved and additional charges that are valid at this time. Preserved charges are mapped to an appropriate charge and are closed to new customers.
- 3.6. Annex 4 contains the charges applied to LDNOs in respect of LV and HV Designated Properties connected in their embedded Distribution System.

## **4. Schedule of line loss factors**

### **Role of line loss factors in the supply of electricity**

- 4.1. Electricity entering or exiting our Distribution System is adjusted to take account of energy that is lost<sup>8</sup> as it is distributed through the network. This adjustment does not affect distribution charges but is used in energy settlement to take metered consumption to a notional grid supply point so that suppliers' purchases take account for the energy lost on the Distribution System.
- 4.2. We are responsible for calculating the Line Loss Factors<sup>9</sup> (LLFs) and providing these to Elexon. Elexon is the company that manages the BSC. This code covers the governance and rules for the balancing and settlement arrangements.
- 4.3. LLFs are used to adjust the metering system volumes to take account of losses on the distribution network.

### **Calculation of line loss factors**

- 4.4. LLFs are calculated in accordance with BSC procedure 128 that determines the principles with which we must comply when calculating LLFs.
- 4.5. LLFs are calculated using either a generic method or a site-specific method. The generic method is used for sites connected at LV or HV and the site-specific method is used for sites connected at EHV or where a request for site-specific LLFs has been agreed. Generic LLFs will be applied as a default to all new EHV sites until sufficient data is available for a site-specific calculation.
- 4.6. ENC currently replicate the host DNO calculated losses.
- 4.7. The Elexon website (<http://www.elexon.co.uk/reference/technical-operations/losses/>) contains more information on LLFs. This page also has links to BSC procedure 128 and to our LLF methodology.

### **Publication of Line loss factors**

- 4.8. The LLFs used in Settlement are published on the Elexon portal website, [www.elexonportal.co.uk](http://www.elexonportal.co.uk). The website contains the LLFs in standard industry data

---

<sup>8</sup> Energy can be lost for technical and non-technical reasons and losses normally occur by heat dissipation through power flowing in conductors and transformers. Losses can also reduce if a customer's action reduces power flowing in the distribution network. This might happen when a customer generates electricity and the produced energy is consumed locally.

<sup>9</sup> Also referred to as Loss Adjustment Factors.

formats and in a summary form. A user guide with details on registering and using the portal is also available.

- 4.9. The BSCP128 sets out the timetable by which LLFs are submitted and audited. The submission and audit occurs between September and December in the year prior to the LLFs becoming effective. Only after the completion of the audit at the end of December and BSC approval are the final LLFs published.
- 4.10. 4.10. Illustrative LLFs based on the latest LLFs are provided in Annex 5 of this statement. These illustrative LLFs are provided with reference to the metered voltage or associated LLFC for generic LLFs and by reference to the LLFCs for site specific LLFs. Each LLF is applicable to a defined time period.





## **5. Notes for Designated EHV Properties**

### **EHV costs**

- 5.1. Not Used
- 5.2. Not Used

### **Charges for new Designated EHV Properties**

- 5.3. Charges for any new Designated EHV Properties calculated after publication of the current statement will be published in an addendum to this statement as and when necessary.
- 5.4. The form of the addendum is detailed in Annex 6 to this statement.
- 5.5. The addendum will be sent to relevant DCUSA parties and published as a revised 'Schedule of Charges and Other Tables' spreadsheet on our website. The addendum will include charge information that under enduring circumstances would be found in Annex 2 and line loss factors that would normally be found in Annex 5.
- 5.6. The new Designated EHV Properties charges will be added to Annex 2 in the next full statement released.

### **Charges for amended Designated EHV Properties**

- 5.7. Where an existing Designated EHV Property is modified and energised in the charging year, we may revise the EHV charges for the modified Designated EHV Property. If revised charges are appropriate, an addendum will be sent to relevant DCUSA parties and published as a revised 'Schedule of Charges and Other Tables' spreadsheet on our website. The modified Designated EHV Property charges will be added to Annex 2 in the next full statement released.

### **Demand-side management**

- 5.8. New or existing Designated EHV Property Customers may wish to offer part of their MIC to be interruptible by us (for active network management purposes other than normal planned or unplanned outages) in order to benefit from any reduced UoS charges calculated using the EDCM.
- 5.9. Several options exist in which we may agree for some or the entire MIC to be interruptible. Under the EDCM the applicable demand capacity costs would be based on the MIC minus the capacity subject to interruption.

5.10. If you are interested in making part or all of your MIC interruptible as an integral irrevocable feature of a new connection or modification to an existing connection you should in the first instance contact our connections function;

- By email [MPAN.Requests@gtc-uk.co.uk](mailto:MPAN.Requests@gtc-uk.co.uk)

You must make an express statement in your application that you have an interest in some or all of the import capacity being interruptible for active network management purposes.

5.11. If you are proactively interested in voluntarily but revocably offering to make some or all of your existing connection's MIC interruptible you should in the first instance contact us at the address in paragraph 1.12.

5.12. A guide to DSM is also available. This provides more information on the type of arrangement that might be put in place should you request to participate in DSM arrangements. This document is available by contacting us at the address in paragraph 1.12.

5.13. As of 1<sup>st</sup> April 2017 ENC does not have any EHV sites.

## **6. Electricity distribution rebates**

- 6.1. We have neither given nor announced any DUoS rebates to Users in the 12 months preceding the date of publication of this revision of the statement.

## **7. Accounting and administration services**

- 7.1. We reserve the right to impose payment default remedies. The remedies are as set out in DCUSA where applicable or else as detailed in the following paragraph.
- 7.2. If any invoices that are not subject to a valid dispute remain unpaid on the due date, late payment interest (calculated at base rate plus 8%) and administration charges may be imposed.
- 7.3. Our administration charges are detailed in the following table. These charges are set at a level which is in line with the Late Payment of Commercial Debts Act which can be viewed on:

<http://www.legislation.gov.uk/uksi/2002/1674/regulation/2/made>

<b>Size of Unpaid Debt</b>	<b>Late Payment Fee</b>
Up to £999.99	£40.00
£1,000 to £9,999.99	£70.00
£10,000 or more	£100.00

## **8. Charges for electrical plant provided ancillary to the grant of use of system**

- 8.1. Currently ENC offers no services under this category.
- 8.2. Not Used

## Appendix 1 - Glossary

1.1. The following definitions, which can extend to grammatical variations and cognate expressions, are included to aid understanding:

Term	Definition
All-the-way Charge	A charge that is applicable to an end user rather than an LDNO. An end user in this context is a Supplier/User who has a registered MPAN or MSID and is using the Distribution System to transport energy on behalf of a Customer.
Balancing and Settlement Code (BSC)	The BSC contains the governance arrangements for electricity balancing and settlement in Great Britain. An overview document is available from <a href="http://www.elexon.co.uk/ELEXON/Documents/trading_arrangements.pdf">www.elexon.co.uk/ELEXON Documents/trading_arrangements.pdf</a> .
Common Distribution Charging Methodology (CDCM)	The CDCM used for calculating charges to Designated Properties as required by standard licence condition 13A of the electricity distribution licence.
Central volume allocation (CVA)	As defined in the BSC.
Customer	<p>A person to whom a User proposes to supply, or for the time being supplies, electricity through an exit point, or from whom, a User or any relevant exempt supplier, is entitled to recover charges, compensation or an account of profits in respect of electricity supplied through an exit point;</p> <p>Or</p> <p>A person from whom a User purchases, or proposes to purchase, electricity, at an entry point (who may from time to time be supplied with electricity as a Customer of that User (or another electricity supplier) through an exit point).</p>
Designated EHV Properties	As defined in standard condition 13B of the electricity distribution licence.
Designated Properties	As defined in standard condition 13A of the electricity distribution licence.

Term	Definition																																																												
Distributor IDs	<p>These are unique IDs that can be used, with reference to the MPAN, to identify your LDNO. The charges for other network operators can be found on their website.</p> <table border="1" data-bbox="643 427 1377 1639"> <thead> <tr> <th data-bbox="643 427 715 495">ID</th> <th data-bbox="715 427 997 495">Distribution Service Area</th> <th data-bbox="997 427 1377 495">Company</th> </tr> </thead> <tbody> <tr> <td data-bbox="643 495 715 535">10</td> <td data-bbox="715 495 997 535">East of England</td> <td data-bbox="997 495 1377 535">UK Power Networks</td> </tr> <tr> <td data-bbox="643 535 715 575">11</td> <td data-bbox="715 535 997 575">East Midlands</td> <td data-bbox="997 535 1377 575">Western Power Distribution</td> </tr> <tr> <td data-bbox="643 575 715 616">12</td> <td data-bbox="715 575 997 616">London</td> <td data-bbox="997 575 1377 616">UK Power Networks</td> </tr> <tr> <td data-bbox="643 616 715 692">13</td> <td data-bbox="715 616 997 692">Merseyside and North Wales</td> <td data-bbox="997 616 1377 692">Scottish Power</td> </tr> <tr> <td data-bbox="643 692 715 732">14</td> <td data-bbox="715 692 997 732">Midlands</td> <td data-bbox="997 692 1377 732">Western Power Distribution</td> </tr> <tr> <td data-bbox="643 732 715 772">15</td> <td data-bbox="715 732 997 772">Northern</td> <td data-bbox="997 732 1377 772">Northern Powergrid</td> </tr> <tr> <td data-bbox="643 772 715 813">16</td> <td data-bbox="715 772 997 813">North Western</td> <td data-bbox="997 772 1377 813">Electricity North West</td> </tr> <tr> <td data-bbox="643 813 715 992">17</td> <td data-bbox="715 813 997 992">Scottish Hydro Electric (and embedded networks in other areas)</td> <td data-bbox="997 813 1377 992">Scottish Hydro Electric Power Distribution plc</td> </tr> <tr> <td data-bbox="643 992 715 1032">18</td> <td data-bbox="715 992 997 1032">South Scotland</td> <td data-bbox="997 992 1377 1032">Scottish Power</td> </tr> <tr> <td data-bbox="643 1032 715 1072">19</td> <td data-bbox="715 1032 997 1072">South East England</td> <td data-bbox="997 1032 1377 1072">UK Power Networks</td> </tr> <tr> <td data-bbox="643 1072 715 1216">20</td> <td data-bbox="715 1072 997 1216">Southern Electric (and embedded networks in other areas)</td> <td data-bbox="997 1072 1377 1216">Southern Electric Power Distribution plc</td> </tr> <tr> <td data-bbox="643 1216 715 1256">21</td> <td data-bbox="715 1216 997 1256">South Wales</td> <td data-bbox="997 1216 1377 1256">Western Power Distribution</td> </tr> <tr> <td data-bbox="643 1256 715 1296">22</td> <td data-bbox="715 1256 997 1296">South Western</td> <td data-bbox="997 1256 1377 1296">Western Power Distribution</td> </tr> <tr> <td data-bbox="643 1296 715 1337">23</td> <td data-bbox="715 1296 997 1337">Yorkshire</td> <td data-bbox="997 1296 1377 1337">Northern Powergrid</td> </tr> <tr> <td data-bbox="643 1337 715 1413">24</td> <td data-bbox="715 1337 997 1413">GTC</td> <td data-bbox="997 1337 1377 1413">Independent Power Networks</td> </tr> <tr> <td data-bbox="643 1413 715 1453">25</td> <td data-bbox="715 1413 997 1453">ESP Electricity</td> <td data-bbox="997 1413 1377 1453">ESP Electricity</td> </tr> <tr> <td data-bbox="643 1453 715 1494">26</td> <td data-bbox="715 1453 997 1494">Energetics</td> <td data-bbox="997 1453 1377 1494">Energetics Electricity Ltd</td> </tr> <tr> <td data-bbox="643 1494 715 1570">27</td> <td data-bbox="715 1494 997 1570">GTC</td> <td data-bbox="997 1494 1377 1570">The Electricity Network Company Ltd</td> </tr> <tr> <td data-bbox="643 1570 715 1639">29</td> <td data-bbox="715 1570 997 1639">Harlaxton Energy Networks</td> <td data-bbox="997 1570 1377 1639">Harlaxton Energy Networks</td> </tr> </tbody> </table>	ID	Distribution Service Area	Company	10	East of England	UK Power Networks	11	East Midlands	Western Power Distribution	12	London	UK Power Networks	13	Merseyside and North Wales	Scottish Power	14	Midlands	Western Power Distribution	15	Northern	Northern Powergrid	16	North Western	Electricity North West	17	Scottish Hydro Electric (and embedded networks in other areas)	Scottish Hydro Electric Power Distribution plc	18	South Scotland	Scottish Power	19	South East England	UK Power Networks	20	Southern Electric (and embedded networks in other areas)	Southern Electric Power Distribution plc	21	South Wales	Western Power Distribution	22	South Western	Western Power Distribution	23	Yorkshire	Northern Powergrid	24	GTC	Independent Power Networks	25	ESP Electricity	ESP Electricity	26	Energetics	Energetics Electricity Ltd	27	GTC	The Electricity Network Company Ltd	29	Harlaxton Energy Networks	Harlaxton Energy Networks
ID	Distribution Service Area	Company																																																											
10	East of England	UK Power Networks																																																											
11	East Midlands	Western Power Distribution																																																											
12	London	UK Power Networks																																																											
13	Merseyside and North Wales	Scottish Power																																																											
14	Midlands	Western Power Distribution																																																											
15	Northern	Northern Powergrid																																																											
16	North Western	Electricity North West																																																											
17	Scottish Hydro Electric (and embedded networks in other areas)	Scottish Hydro Electric Power Distribution plc																																																											
18	South Scotland	Scottish Power																																																											
19	South East England	UK Power Networks																																																											
20	Southern Electric (and embedded networks in other areas)	Southern Electric Power Distribution plc																																																											
21	South Wales	Western Power Distribution																																																											
22	South Western	Western Power Distribution																																																											
23	Yorkshire	Northern Powergrid																																																											
24	GTC	Independent Power Networks																																																											
25	ESP Electricity	ESP Electricity																																																											
26	Energetics	Energetics Electricity Ltd																																																											
27	GTC	The Electricity Network Company Ltd																																																											
29	Harlaxton Energy Networks	Harlaxton Energy Networks																																																											
Distribution Connection and Use of System Agreement (DCUSA)	<p>The DCUSA is a multi-party contract between the licensed electricity distributors, suppliers, generators and Offshore Transmission Owners of Great Britain.</p> <p>It is a requirement that all licensed electricity distributors and suppliers become parties to the DCUSA.</p>																																																												

<b>Term</b>	<b>Definition</b>
Distribution Network Operator (DNO)	An electricity distributor that operates one of the 14 distribution services areas and in whose electricity distribution licence the requirements of Section B of the standard conditions of that licence have effect.
Distribution Services Area	The area specified by the Gas and Electricity Markets Authority within which each DNO must provide specified distribution services.
Distribution System	<p>The system consisting (wholly or mainly) of electric lines owned or operated by an authorised distributor that is used for the distribution of electricity from:</p> <ul style="list-style-type: none"> <li>• Grid Supply Points or generation sets or other entry points</li> </ul> <p>to the points of delivery to:</p> <ul style="list-style-type: none"> <li>• Customers or Users or any transmission licensee in its capacity as operator of that licensee's transmission system or the Great Britain (GB) transmission system and includes any remote transmission assets (owned by a transmission licensee within England and Wales)</li> </ul> <p>that are operated by that authorised distributor and any electrical plant, electricity meters, and metering equipment owned or operated by it in connection with the distribution of electricity, but does not include any part of the GB transmission system.</p>
EHV Distribution Charging Methodology (EDCM)	The EDCM used for calculating charges to Designated EHV Properties as required by standard licence condition 13B of the Electricity Distribution Licence.
Electricity Distribution Licence	The Electricity Distribution Licence granted or treated as granted pursuant to section 6(1) of the Electricity Act 1989.
Electricity Distributor	Any person who is authorised by an Electricity Distribution Licence to distribute electricity.
Embedded LDNO	This refers to an LDNO operating a distribution network which is embedded within another distribution network.
Embedded Network	An electricity Distribution System operated by an LDNO and embedded within another distribution network.

<b>Term</b>	<b>Definition</b>
Entry Point	A boundary point at which electricity is exported onto a Distribution System from a connected installation or from another Distribution System, not forming part of the total system (boundary point and total system having the meaning given to those terms in the BSC).
Exit Point	A point of connection at which a supply of electricity may flow from the Distribution System to the Customer's installation or User's installation or the Distribution System of another person.
Extra-High Voltage (EHV)	Nominal voltages of 22kV and above.
Gas and Electricity Markets Authority (GEMA)	As established by the Utilities Act 2000.
Grid Supply Point (GSP)	A metered connection between the National Grid Electricity Transmission system and the licensee's distribution system at which electricity flows to or from the Distribution System.
GSP group	A distinct electrical system that is supplied from one or more GSPs for which total supply into the GSP group can be determined for each half hour.
High Voltage (HV)	Nominal voltages of at least 1kV and less than 22kV.
Invalid Settlement Combination	A Settlement combination that is not recognised as a valid combination in market domain data - see <a href="https://www.elexonportal.co.uk/MDDVIEWER">https://www.elexonportal.co.uk/MDDVIEWER</a> .
kVA	Kilovolt amperes.
kVArh	Kilovolt ampere reactive hour.
kW	Kilowatt.
kWh	Kilowatt hour (equivalent to one "unit" of electricity).
Licensed Distribution Network Operator (LDNO)	The holder of a licence in respect of distribution activities in Great Britain.
Line Loss Factor (LLF)	The factor that is used in Settlement to adjust the metering system volumes to take account of losses on the Distribution System.
Line Loss Factor Class (LLFC)	An identifier assigned to an SVA metering system which is used to assign the LLF and use of system charges.



Term	Definition
Load Factor	$= \frac{\text{annual consumption (kWh)}}{\text{maximum demand (kW)} \times \text{hours in year}}$
Low Voltage (LV)	Nominal voltages below 1kV.
Market Domain Data (MDD)	MDD is a central repository of reference data available to all Users involved in Settlement. It is essential to the operation of SVA trading arrangements.
Maximum Export Capacity (MEC)	The MEC of apparent power expressed in kVA that has been agreed can flow through the entry point to the Distribution System from the Customer's installation as specified in the connection agreement.
Maximum Import Capacity (MIC)	The MIC of apparent power expressed in kVA that has been agreed can flow through the exit point from the Distribution System to the Customer's installation as specified in the connection agreement.
Measurement Class	<p>A classification of metering systems used in the BSC which indicates how consumption is measured, i.e.:</p> <ul style="list-style-type: none"> <li>• Measurement class A – non-half-hourly metering equipment;</li> <li>• Measurement class B – non-half-hourly unmetered supplies;</li> <li>• Measurement class C – half-hourly metering equipment at or above 100kW premises;</li> <li>• Measurement class D – half-hourly unmetered supplies; and</li> <li>• Measurement class E – half-hourly metering equipment below 100kW premises, and from 5 November 2015, with current transformer.</li> <li>• Measurement class F – half hourly metering equipment at below 100kW premises with current transformer or whole current, and at domestic premises</li> <li>• Measurement class G – half hourly metering equipment at below 100kW premises with whole current and not at domestic premises</li> </ul>
Meter Timeswitch Code (MTC)	MTCs are three digit codes allowing suppliers to identify the metering installed in Customers' premises. They indicate whether the meter is single or multi-rate, pre-payment or credit, or whether it is 'related' to another meter. Further information can be found in MDD.

<b>Term</b>	<b>Definition</b>
Metering Point	The point at which electricity that is exported to or imported from the licensee's Distribution System is measured, is deemed to be measured, or is intended to be measured and which is registered pursuant to the provisions of the MRA. For the purposes of this statement, GSPs are not 'metering points'.
Metering Administration Point Number (MPAN)	A number relating to a Metering Point under the MRA.
Metering System	Particular commissioned metering equipment installed for the purposes of measuring the quantities of exports and/or imports at the exit point or entry point.
Metering System Identifier (MSID)	MSID is a term used throughout the BSC and its subsidiary documents and has the same meaning as MPAN as used under the MRA.
Master Registration Agreement (MRA)	The MRA is an Agreement that sets out terms for the provision of Metering Point Administration Services (MPAS) Registrations, and procedures in relation to the Change of Supplier to any premise/metering point.
Nested Networks	This refers to a situation where there is more than one level of Embedded Network and therefore nested Distribution Systems between LDNOs (e.g. host DNO→primary nested DNO→ secondary nested DNO→customer).
Ofgem	Office of Gas and Electricity Markets – Ofgem is governed by GEMA and is responsible for the regulation of the distribution companies.
Profile Class (PC)	A categorisation applied to NHH MPANs and used in Settlement to group Customers with similar consumption patterns to enable the calculation of consumption profiles.
Settlement	The determination and settlement of amounts payable in respect of charges (including reconciling charges) in accordance with the BSC.
Settlement Class (SC)	The combination of Profile Class, Line Loss Factor Class, Time Pattern Regime and Standard Settlement Configuration, by Supplier within a GSP group and used for Settlement.

<b>Term</b>	<b>Definition</b>
Standard Settlement Configuration (SSC)	A standard metering configuration relating to a specific combination of Time Pattern Regimes.
Supercustomer	The method of billing Users for use of system on an aggregated basis, grouping together consumption and standing charges for all similar NHH metered Customers or aggregated HH metered Customers.
Supercustomer DUoS Report	A report of profiled data by Settlement Class providing counts of MPANs and units consumed.
Supplier	An organisation with a supply licence responsible for electricity supplied to and/or exported from a metering point.
Supplier Volume Allocation (SVA)	As defined in the BSC.
Time Pattern Regime (TPR)	The pattern of switching behaviour through time that one or more meter registers follow.
Unmetered Supplies	Exit points deemed to be suitable as unmetered supplies as permitted in the Electricity (Unmetered Supply) Regulations 2001 and where operated in accordance with BSC procedure 520 <sup>10</sup> .
Use of System Charges	Charges which are applicable to those parties which use the Distribution System.
User	Someone that has a use of system agreement with the DNO e.g. a supplier, generator or other DNO.

---

<sup>10</sup> Balancing and Settlement Code Procedures are available from <http://www.elexon.co.uk/pages/bscps.aspx>

## **Appendix 2 - Guidance notes<sup>11</sup>**

### **Background**

- 1.1. The electricity bill from your Supplier contains an element of charge to cover electricity distribution costs. This distribution charge covers the cost of operating and maintaining a safe and reliable Distribution System that forms the 'wires' that transport electricity between the national transmission system and end users such as homes and businesses. Our Distribution System includes overhead lines, underground cables, as well as substations and transformers.
- 1.2. In most cases, your Supplier is invoiced for the distribution charge and this is normally part of your total bill. In some cases, for example business users, the supplier may pass through the distribution charge as an identifiable line item on the electricity bill.
- 1.3. Where electricity is generated at a property your Supplier may receive a credit for energy that is exported on to the Distribution System. These credits are intended to reflect that the exported generation may reduce the need for traditional demand led reinforcement of the Distribution System.
- 1.4. Understanding your distribution charges could help you reduce your costs and increase your credits. This is achieved by understanding the components of the charge to help you identify whether there may be opportunities to change the way you use the Distribution System.

### **Meter point administration**


- 1.5. We are responsible for managing the electricity supply points that are connected to our Distribution System. Typically every supply point is identified by a Meter Point Administration Number (MPAN). A few supply points may have more than one MPAN depending on the metering configuration (e.g. a school which may have an MPAN for the main supply and a MPAN for catering).
- 1.6. The full MPAN is a 21 digit number, preceded by an 'S'. The MPAN applicable to a supply point is found on the electricity bill from your Supplier. This number enables you to establish who your electricity distributor is, details of the characteristics of the supply and importantly the distribution charges that are applicable to your premise.

---

<sup>11</sup> These guidance notes are provided for additional information and do not form part of the application of charges.

1.7. The 21-digit number is normally presented in two sections as shown in the following diagram. The top section is supplementary data which gives information about the characteristics of supply, while the bottom 'core' is the unique identifier.

Full MPAN diagram



1.8. Generally, you will only need to know the Distributor ID and line loss factor class to identify the distribution charges for your premise. However, there are some premises where charges are specific to that site. In these instances the charges are identified by the core MPAN. The Distributor ID for ETCL is 27. Other Distributor IDs can be referenced in the glossary.

1.9. Additionally it can be useful to understand the profile class provided in the supplementary data. The profile class will be a number between 00 and 08. The following list provides details of the allocation of profile classes to types of customers:

- '01' – Domestic customers with unrestricted supply
- '02' – Domestic customers with restricted load, for example off-peak heating
- '03' – Non-domestic customers with unrestricted supply
- '04' – Non-domestic customers with restricted load, for example off-peak heating
- '05' – Non-domestic maximum demand customers with a Load Factor of less than 20%
- '06' – Non-domestic maximum demand customers with a Load Factor between 20% and 30%

- '07' – Non-domestic maximum demand customers with a Load Factor between 30% and 40%
- '08' – Non-domestic maximum demand customers with a Load Factor over 40% or non-half-hourly metered generation customers
- '00' – Half-hourly metered demand and generation customers

1.10. Unmetered Supplies will be allocated to profile class 01, 08 and 00 depending on the type of load or the measurement method of the load.

1.11. The allocation of the profile class will affect your charges. If you feel that you have been allocated the wrong profile class, please contact your Supplier as they are responsible for this.

### **Your charges**

1.12. All distribution charges that relate to our Distributor ID 27 are provided in this statement.

1.13. You can identify your charges by referencing your line loss factor class, from Annex 1. If the MPAN is for a Designated EHV Property then the charges will be found in Annex 2. In a few instances, the charges may be contained in Annex 3. When identifying charges in Annex 2, please note that some line loss factor classes have more than one charge. In this instance you will need to select the correct charge by cross referencing with the core MPAN provided in the table.

1.14. Once you have identified which charge structure applies to your MPAN then you will be able to calculate an estimate of your distribution charge using the calculator provided in the spreadsheet 'Schedule of charges and other tables' found in the sheet called 'Charge Calculator'. This spreadsheet can be downloaded from <http://www.gtc-uk.co.uk/about-us/our-regulated-businesses>.

### **Reducing your charges**

1.15. The most effective way to reduce your energy charges is to reduce your consumption by switching off or using more energy efficient appliances. However, there are also other potential opportunities to reduce your distribution charges; for example, it may be beneficial to shift demand or generation to a better time period. Demand use is likely to be cheaper outside peak periods and generation credits more beneficial, although the ability to directly benefit will be linked to the structure of your supply charges.

1.16. The calculator mentioned above provides the opportunity to establish a forecast of the change in distribution charges that could be achieved if you are able to change any of the consumption related inputs.

## **Reactive power and reactive power charges**

- 1.17. Reactive power is a separately charged component of connections that are half-hourly metered. Reactive power charges are generally avoidable if 'best practice' design of the properties' electrical installation has been provided in order to maintain a power factor between 0.95 and unity at the Metering Point.
- 1.18. Reactive Power (kVArh) is the difference between working power (active power measured in kW) and total power consumed (apparent power measured in kVA). Essentially it is a measure of how efficiently electrical power is transported through an electrical installation or a Distribution System.
- 1.19. Power flowing with a power factor of unity results in the most efficient loading of the Distribution System. Power flowing with a power factor of less than 0.95 results in much higher losses in the Distribution System, a need to potentially provide higher capacity electrical equipment and consequently a higher bill for you the consumer. A comparatively small improvement in power factor can bring about a significant reduction in losses since losses are proportional to the square of the current.
- 1.20. Different types of electrical equipment require some 'reactive power' in addition to 'active power' in order to work effectively. Electric motors, transformers and fluorescent lighting, for example, may produce poor power factors due to the nature of their inductive load. However, if good design practice is applied then the poor power factor of appliances can be corrected as near as possible to source. Alternatively poor power factor can be corrected centrally near to the meter.
- 1.21. There are many advantages that can be achieved by correcting poor power factor. These include: reduced energy bills through lower reactive charges, lower capacity charges and reduced power consumption and reduced voltage drop in long cable runs.

## **Site-specific EHV charges**

- 1.22. ENC does not have any EHV sites

**Annex 1 - Schedule of Charges for use of the Distribution System by LV and HV Designated Properties**

**Annex 2 - Schedule of Charges for use of the Distribution System by Designated EHV Properties (including LDNOs with Designated EHV Properties/end-users).**

ENC does not have any customers connected at EHV at this time.

**Annex 3 - Schedule of Charges for use of the Distribution System to Preserved/Additional LLFC Classes**

ENC does not have any customers on preserved tariffs.

**Annex 4 - Charges applied to LDNOs with HV/LV end users**

**Annex 5 – Schedule of Line Loss Factors**

**Annex 6 - Un-scaled [nodal /network group] costs**

As ENC operates across all DNO areas, spreadsheets for the Annexes detailed above have been created for each DNO area, and are available to download from <http://www.gtc-uk.co.uk/about-us/our-regulated-businesses>. This document is also available by contacting us at the address in paragraph 1.12.